



Installation Instructions



PRODUCT: 4.5" Game Changer Suspension, Fox Edition

REV: G | 06-19-2019 | II-7129

READ INSTRUCTIONS IN FULL BEFORE INSTALLATION.
QUESTIONS? CALL 916-631-8071 M-F 7:00 AM – 5:00 PM PST

The MetalCloak experience includes the ease of installation of our products. We design for most contingencies, but installation may be different based on different Jeep condition, configuration and/or year.

We are continually trying to improve our products and instructions – please help us by providing feedback and pictures if you find any part of the instructions that do not match your particular Jeep or are not easily understandable.

If you have any difficulties at all, please give us a call. Thank you and enjoy your MetalCloak Products!

IMPORTANT NOTE: We use Stainless Steel Hardware where possible. Therefore, a tube of Silver Anti-seize is provided and should be used on all bolts—only a small amount is needed.

WARRANTY INFORMATION: This article is sold without warranty expressed or implied. No warranty or representation is made as to this products ability to protect the user from injury or death. The user assumes that risk. The effectiveness, warranty and longevity of this equipment are directly related to the manner in which it is INSTALLED, USED and/or MAINTAINED. THE USER ASSUMES ALL RISK. By purchasing this product and opening the packaging, purchasers expressly acknowledge, understand and agree that they take, select and purchase these MetalCloak products from Armored Works, LLC, its affiliates and distributors and agents as is and with all faults. The entire risk as to the quality and performance of these MetalCloak products is with the purchaser. Working on your vehicle can be a dangerous activity. If you are unsure of what you are doing, please leave mechanical or safety critical work to a skilled mechanic. We take no responsibility for the incorrect use and/or installation of MetalCloak products.

Section 1: Tools & Notes on Installation



Tools Required: This list is the recommended tools for ease of installation. Other versions of the same tool can be used. For example, Allen Wrenches instead of Allen Drive Sockets. Be sure to use metric on metric and SAE on SAE.



Socket & Ratchet Wrench

Metal Head Hammer




10" Socket Extension

Electric Drill



Center Punch

Philips Screwdriver



Retaining Ring Pliers

5/16" Allen Drive Socket
10mm Allen Drive Socket



Cut-Off Disc and Grinder
(Optional)

12mm Brake line Wrench
17mm Brake line Wrench



10mm Socket	12mm Socket
14mm Socket	15mm Socket
16mm Socket	18mm Socket
1/2" Socket	5/8" Socket
3/4" Socket	13/16" Socket
7/8" Socket	21mm Socket
22mm Socket	19mm Socket

12mm Wrench	14mm Wrench
17mm Wrench	18mm Wrench
19mm Wrench	1-1/2" Wrench
1-7/8" Wrench	3/4" Wrench
9/16" Wrench	3/8" Wrench
5/8" Wrench	9/32" Wrench
1/2" Wrench	



3/8" Drill Bit	L Drill Bit
1/4" Drill Bit	1/2" Drill Bit
7/16" Drill Bit	9/16 Drill Bit
7/8" Drill Bit	

Section 1: Tools & Notes on Installation



HOW TO USE THIS GUIDE: The installation guide contains ALL steps for installation. Please read and follow the instructions in order of each page top to bottom, and left to right.

Jeep Model: Instructions may apply to multiple Jeep models, but are labeled separately where appropriate (i.e. TJ vs. LJ).

Options: Because of the number of component options we offer, these instructions may contain steps that will not match your particular configuration. You can skip these steps.

Images: Pictures are provided and parts are labeled throughout the instructions. Each text box contains guidance based on the pictures next to it. The text will refer to alphabetical labels (A, B, etc) found in the images.

Installation Notes: Terms may be used in the body of the instructions that you may not be familiar with, if you have any questions feel free to contact us at the number below, or email techhelp@metalcloak.com

QUESTIONS: Any questions or comments about the instructions? Call us at 916-631-8071 M-F 7:00 AM – 5:00 PM PST.

Section 4: Product Components




DC-0001 REV A

SHEET 1 OF 1

ITEM	PART NUMBER/DESCRIPTION	QTY.
1	1005 BDS PERFORMANCE SHOCK, FOX 4.5IN FRONT JK, PAIR	1
2	1006 BDS PERFORMANCE SHOCK, FOX 4.5IN REAR JK, PAIR	1
3	1101 BRAKEQUIP KIT, JK FRONT-REAR 24.5L	2
4	7012 TRACK BAR MOUNT KIT, REAR JK	1
5	7040 BUMP STOP KIT, 1.0-4.0 JK FRONT	1
6	7043 BUMP STOP KIT, 1.0-4.0 REAR	1
7	7097 DRAG LINK FLIP KIT, JK	1
8	7104 OUTBOARD SHOCK MOUNT KIT, LOWER FRONT JK	1
9	7105 DUROFLEX CONTROL ARM KIT, JK	1
10	7242 TRACK BARS, JK FRONT+REAR	1

- D** OPTION 1 (REAR SWAY BAR)
 STOCK WHEELS (BACKSPACING > 5.5")
 7026 SWAY BAR DROP BRACKET KIT, JK REAR
 AFTERMARKET WHEELS (BACKSPACING < 5.5")
 7270 SWAY BAR LINK KIT, 12.25IN REAR
- C** OPTION 2 (FRONT SWAY BAR)
 RUBICON (RELEASABLE SWAY BAR)
 7015 SWAY BAR LINK KIT, 12.25IN FRONT
 NON RUBICON (SOLID SWAY BAR)
 7014 SWAY BAR QUICK DISCONNECT, 12.25 INCH JK
- B** OPTION 3
 2 DOOR
 7084 DUAL RATE COIL SPRING SET, 4.5IN JK 2DR
 4 DOOR UNLIMITED
 7070 DUAL RATE COIL SPRING SET, 4.5IN JK 4DR



A

THE INFORMATION CONTAINED ON THIS DRAWING IS THE EXCLUSIVE PROPERTY OF ARMORED WORKS, LLC. UNAUTHORIZED REPRODUCTION IS PROHIBITED.
DO NOT SCALE DRAWING



PART NUMBER DESCRIPTION 7129 DUROFLEX SUSPENSION SYSTEM, 4.5IN JK, FOX SHOCK

Section 2: Installation Instructions





Important Note: MetalCloak does not recommend powder coating your True Dual Rate Coils. The baking process in powder coating can, in some cases, cause the metallurgical properties of the coils to be changed, resulting in the loss of the lift properties of the coils. As such, the process of powder coating the coils will void any warranty stated or implied in relation to the coils.


Important Note: To install lift components you will need to fully 'droop' your suspension in the front and rear (not at the same time). We strongly recommend that the vehicle be placed on an automotive lift and that all appropriate safety precautions be taken to secure the vehicle while it is off the ground. Always use the necessary axle stands (or equivalent) to support the axle when the suspension components are disconnected for safety, and to ensure the integrity of your suspension system during the installation process.

Important Note: If using stock wheels with factory backspacing the #7104 outboard shock mount is not recommended as it will interfere with the wheel.

Important Note: MetalCloak provides "rear specific" end-links that have shorter bolt lengths that will keep for optimal fitment.




Section 2: FRONT SUSPENSION Installation Instructions



Important Note: To prevent tires from rubbing the shocks at full turn and flex, a clearance of 11-3/4" between inner wall of the tire and the outside of the frame rail is recommended. Wheel backspacing, wheel spacers, axle width and tire width can effect this value. We recommend a wheel backspacing of less than or equal to 4.0" for most common vehicle builds.

Step 1: Remove Stock Components

- Disconnect front sway bar links.
- Watch the brake lines as the axle drops! Unbolt the bracket from the frame and axle in case the lines are stretched while working.
- Remove the front track bar.




Section 2: FRONT SUSPENSION Installation Instructions



Step 1: Remove Stock Components

- D. Use a 16MM (5/8") Socket and Wrench to remove the stock nut on top of the upper shock mount tower.
- E. Use a 19MM (3/4") Socket and Wrench to remove the stock nut and bolt from the lower shock mount bracket located on the axle.
- F. Remove stock springs, and any spacers that have been used if vehicle has been previously lifted.





Section 2: FRONT SUSPENSION Installation Instructions



Step 2: Install Front Brake Line

- A. Use a 15mm Socket to remove the 'banjo' bolt from the brake calipers. You will want an oil drain pan to catch the brake fluid.
- B. Unclip the ABS line from the brake line (all the way down), and use a 10mm Socket to remove the bolt holding the stock bracket. Remove the frame clip and discard.
- C. Use a 12mm Wrench to unscrew the stock brake line from the frame bracket.




Section 2: FRONT SUSPENSION Installation Instructions



Step 2: Install Front Brake Line

- D. Place the L-bracket on the frame in the factory location using the factory hardware.
- E. Install the 24-1/2" Brake Line through the bracket.
- F. Screw the stock line into the new Brake Line, and tighten using a 12mm and 17mm Wrench.
- G. Install the provided Spring Clip to retain the Brake Line in the Bracket. You may need a hammer to lightly tap this clip into place.
- H. Use a 1/2" Socket to install the 5/16"-18 Hex Head Self-Tapping Screw. Do not fully tighten.
- I. Feed the banjo bolt through the square end of the brake line. Use the provided brass washers on both sides of the brake line as shown.
- J. Re-install the banjo bolt into the brake caliper.
- K. Zip-tie the ABS lines to the new brake lines.





Section 2: FRONT SUSPENSION Installation Instructions



Step 3: Swap Front Control Arms

- A. Use an 18mm Socket & Wrench to remove the stock bolts. You will need a socket extension to access the head of the upper bolt inside the frame [A1].
- B. The exhaust on the passenger side of some models interferes with removal of the upper bolt. Cut the stock bolt and replace it with the Flange Hex Head Bolt and Hex Flange Nut provided, install bolt from the outside of frame and the nut inside the frame.
- C. Use a 21mm Socket and Wrench to remove the stock hardware and control arms; re-use this hardware to install the MetalCloak Front Lower Control Arms.
- D. Install the Control Arms so that the short bend (with the LockNut) is in the rear, and the arm angles INBOARD to provide tire turning clearance.



Section 2: FRONT SUSPENSION Installation Instructions



Step 3: Swap Front Control Arms

CONTROL ARM SPECIFICATIONS...

	Caster Angle	Front Control Arms		Rear Control Arms	
		Lower	Upper	Lower	Upper
Factory Control Arms	Stock	22 5/8"	18 3/4"	19 3/4"	17 7/16"
MetalCloak 2.5" - 3.5" Lift	5 Degrees	23 1/16"	18 3/4"	20 7/16"	18 7/16"
MetalCloak 4.5" - 5.5" Lift	5 Degrees	23 9/16"	19 1/4"	20 15/16"	18 15/16"

Vehicle Setup: the chart below is not definitive, but is provided as a resource for the purpose of guidance and planning. Your individual build may require addition or removal of Bump Stop Pucks to achieve the ideal geometry setup.

2007+ Jeep Wrangler JK with Recommended Old Man Emu Long Travel Shocks					
	Tire Size				
	31"	33"	35"	37"	40"
MetalCloak High Clearance Overline Fenders	2"	2"	2"	3"	4"
MetalCloak Overland Fenders	2"	2"	3"	4"	NR
Stock Fenders (not trimmed)	2"	3"	4"	NR	NR
Generic Aftermarket Fenders (Poison Spyder, Xenon, Bushwacker)	2"	2"	3"	4"	NR


NR = Not Recommended

Section 2: FRONT SUSPENSION Installation Instructions




Step 4: Remove Springs

- A. Droop your suspension and remove your springs to gain access to the spring perch. This process may include disconnecting shocks, sway-bar links, track-bar, and/or steering drag link.



Step 5: Drill Spring Cup

- B. Center a Bump Stop Disk on the top of the spring perch and mark the center of the hole.
- C. Drill a hole at the marked location. You can use any drill size from size 1/2" to size 9/16".





Section 2: FRONT SUSPENSION Installation Instructions



Step 6: Install Bump Stop

- D. Select the appropriate Screw length so that the threads stick out of the bottom Disks approximately $\frac{3}{4}$ ". Assemble your bump stops by feeding the $\frac{1}{2}$ " Countersunk Screw through the Cover Plate, and then threading through the Bump Stop Disks. The center hole in the Disk is intentionally small to create the most rigid assembly possible after installation.
- E. **IMPORTANT!** Place the assembled Bump Stop inside the spring before re-installing. Re-install the spring and place the end of the $\frac{1}{2}$ " Screw in the drilled hole.
- F. The $\frac{1}{2}$ " Screw is backed by a $\frac{1}{2}$ " Flanged Nylon Lock Nut. Install the nut and tighten the hardware using a $\frac{5}{16}$ " Hex Key Socket or Allen Wrench and a $\frac{3}{4}$ " Wrench. Tighten until everything is tight; the hardware will not bottom out, but instead will begin to compress the Disks.
- G. Repeat all steps for other side, and then re-install all other suspension components.



Section 2: FRONT SUSPENSION Installation Instructions



Step 7: Install Front Coils



- H. If the axle does not “droop” enough to allow the coil to be put in place a coil compressor can be used to compress the coil to allow fitment.
- I. Install Front Dual Rate Coils with the tightly wound coils oriented upward.
- J. Slip the bottom of the coil onto the coil base on the axle.



Section 3: Installation Instructions

Step 1: Disconnect stock components




- A. Disconnect the axle mount side of the steering stabilizer *(If you have an aftermarket steering stabilizer mount, disconnect the mount).*
- B. Place the Flip Kit Mount over the top of the Axle
- C. Hand Tighten U-Bolt.



Section 3: Installation Instructions

Step 2: Install flip bracket


- D. Insert the bottom bolt spacer.
- E. Using a 10mm Allen Socket and a 22mm wrench install the bottom bolt.
- F. Adjust Track Bar.
- G. Install track bar using a 14mm socket and a 22mm wrench.
- H. Tighten the U-bolt nuts using a 19mm socket.




Note: It is helpful to have someone push the vehicle to the driver or passenger side to help align the hole; if you don't have an extra pair of hands you can use a ratchet strap on the frame/axle to pull the frame in the desired direction. Check to ensure the axle is centered once the bolt is in place. If not then remove the bolt, adjust the Track Bar length, replace the bolt, and re-check axle centeredness. Repeat until the axle is as close to center.

Section 3: Installation Instructions

Step 3: Install Drag Link



- I. Install the steering stabilizer mount bolt and nut 9/16" wrench and socket (*insert the nut between the original steering stabilizer mount location*).
- J. Remove the pin from the passenger side drag link bushing.
- K. Using a adjustable wrench disconnect the drag link nut.
- L. Using a 7/8" drill bit drill out the drag link knuckle.



Section 3: Installation Instructions

Step 3: Install Drag Link




M. Insert spacer into drilled out hole.

N. Flip drag link and install into knuckle.

O. Tighten down drag link nut using an adjustable wrench

P. Install knuckle pin

Q. Install the steering stabilizer into the steering stabilizer mount (*Install the bolt with the nut on top and tighten with a 19mm socket and wrench*).







Section 3: Installation Instructions

Step 9: Install Outboard Shock Spacer Kit

Important Note: If using stock wheels with factory backspacing the outboard shock mount is not recommended as it will interfere with the wheel.



- A. Slide the stock shock bracket into the outboard shock spacer making sure the holes align.
- B. Mark the hole located on the bottom of the shock mount.
- C. Drill out all three holes using a 3/8" drill bit.



Section 3: Installation Instructions

Step 9: Install Outboard Shock Spacer Kit



- D. Install 2 bottom bolts hand tight.
- E. Install the side bolt hand tight
- F. Insert the spacer in the space between the stock shock mount.
- G. Install spacer bolt and washers.
- H. Tighten all hardware.
Flange Bolts – 14MM Socket & Wrench
Hex Bolts – 19MM Socket & Wrench



Section 3: Installation Instructions

Step 8: Install Fox Shocks


- A. Install the Fox front shocks (Part # 98224922). Put the upper shock pin through the upper tower first and bolt into place (do not tighten). It may be necessary to grind some of the plastic engine guard components above the shock tower.
- B. Align the shock with the outboard shock spacer.
- C. Install stock hardware.
- D. Using a 18mm wrench and socket tighten stock hardware.
- E. Torque all bolts to 35 ft/lbs.



Section 3: Installation Instructions

Step 10: Install JK Front Track Bar

- A. Remove stock track bar. Set the hardware aside for re-use.
- B. The fixed end of the MetalCloak JK Front Track Bar goes in the stock frame bracket. The clearance bends should point toward the front bumper, up and away from the differential cover. Re-use the stock hardware, and only hand tighten the hardware for now (you will fully tighten everything at the end).
- C. The adjustable end of the Track Bar goes into the drag link bracket on the axle, again re-using the stock hardware. With the full weight of the vehicle on the springs, push the bolt through the bracket and the Track Bar joint.
- D. Fully tighten the stock hardware on both ends of the Track Bar, and then tighten the Jam Nut on the Track Bar.
- E. MetalCloak **STRONGLY RECOMMENDS** having your alignment checked by a professional after changing any suspension components.






Note: It is helpful to have someone push the vehicle to the driver or passenger side to help align the hole; if you don't have an extra pair of hands you can use a ratchet strap on the frame/axle to pull the frame in the desired direction. Check to ensure the axle is centered once the bolt is in place. If not then remove the bolt, adjust the Track Bar length, replace the bolt, and re-check axle centeredness. Repeat until the axle is as close to center.

Section 2: FRONT SUSPENSION Installation Instructions

Step 10: Install Sway Bar Links

- A. Install the lower quick disconnect pin in the stock location. Point the pin toward the center of the vehicle, backed by the provided $\frac{1}{2}$ "-13 hardware. A screwdriver through the hole on the end of the pin is helpful while tightening the nut with a $\frac{3}{4}$ " wrench.
- B. Assemble the sway bar link by threading a jam nut onto the lower link.
- C. Now thread the link into the ball joint. Set the length to 12.25". Do not tighten Jam nut yet.
- D. Install the ball joint on the outside of the sway bar end. You will need a thin $\frac{9}{16}$ " box end wrench to keep the ball joint from turning while you tighten the nut with a $\frac{5}{8}$ " wrench.





Section 2: FRONT SUSPENSION Installation Instructions



Step 10: Install Sway Bar Links

- E. Installed lower rubber bushing on the quick disconnect pin.
- F. Tighten the jam nut.
- G. Disconnect the links and align the provided brackets in the desired location. There is no exact location; the goal is simply to keep the sway bar clear of the tires when stowed. Mark the locations and drill with a 9/32" drill bit. Install the self-tapping screws through the bracket using a 1/2" wrench.
- H. Re-attach the links to the lower pins and install the 1/4" Locking Pins. These may be snug against the rubber bushing, so don't be surprised if you need to use a little muscle to push them through.



Section 2: FRONT SUSPENSION Installation Instructions



Step 11: Finalize Installation

- A. Adjust the caster angle and toe as needed. Once set, tighten all hardware. Finally, tighten the jam nuts on all control arms.

Section 3: REAR SUSPENSION Installation Instructions



Note: When lifting any vehicle, basic dynamics are changed. It is important for you to take your vehicle to a professional for alignment after installation. When doing so, make sure he is setting caster for lifted vehicle (not stock specs).

Step 1: Remove Stock Components

- A. Disconnect rear sway bar links.
- B. Disconnect rear brake lines. Go ahead and replace the brake lines at this time.
- C. Remove the rear track bar.
- D. Remove the shocks.
- E. Remove stock springs, and any spacers that have been used if vehicle has been previously lifted.





Section 3: REAR SUSPENSION Installation Instructions



Step 2: Rear Control Arms

- A. Use a 21mm socket and wrench to remove the stock hardware and control arms; re-use this hardware to install MetalCloak rear control arms. The LockNuts should be towards the front, at the frame mount for both upper and lower control arms.
- B. The MetalCloak rear upper arm should be oriented so that the bend in the arm angles inboard to provide tire clearance.




Section 2: REAR SUSPENSION Installation Instructions



Step 3: Install Rear Coils

- A. If the axle does not “droop” enough to allow the coil to be put in place a coil compressor can be used to compress the coil to allow fitment.
- B. Place the Rear Coil Cup on top of the Rear Dual Rate Coil.
- C. Install Rear Dual Rate Coils with the tightly wound coils oriented downward.
- D. Slip the bottom of the coil onto the coil base on the axle.



Section 3: Installation Instructions

Step 7: Rear Fox Shocks

- A. Install the Fox Rear Shocks (Part # 98224959). Using the stock hardware from removal of stock rear shock, install the Bar Pin side of the Fox Rear Shock in the upper tub side bolt hole mounts and tight bolts.
- B. Slip the bottom shock mount into the axle mounting bracket (C) and slide the bolt through (you may need to compress the shock to fit).
- C. Tighten all bolts.



Section 3: REAR SUSPENSION Installation Instructions



Step 5: Install Front Brake Line

- A. The steps to replace the rear brake lines are essentially identical to the front. The only difference is that in the upper rear you will re-use the stock screw and frame clip. Use the M6 screw to install the L-Bracket in the stock location, and then install the Brake Line following the same steps as the front.




Step 6: Bleed Brakes


CAUTION!! FAILURE TO PROPERLY BLEED THE BRAKE LINES WILL CAUSE YOUR BRAKES TO BE INEFFECTIVE. Before your vehicle is ready to drive you will need to refill the brake reservoir and bleed the air out of the brake lines. If you are not experienced with this process, or have any reservations, consult a professional. For a full write-up of the brake bleeding process for your JEEP Wrangler JK, you can also refer to <http://project-jk.com/jeep-jk-write-ups/jeep-jk-wrangler-maintenance-bleeding-your-brakes>.

Section 3: REAR SUSPENSION Installation Instructions

Step 7: Install Rear Bump Stops



- A. Driver Side Bump Stop Holes.
- B. Passenger Side Bump Stop Holes.
- C. Diagram showing the two sides of the Bump Stops.



Section 3: REAR SUSPENSION Installation Instructions



Step 7: Install Rear Bump Stops

D. Install first bump stop puck (Side A) using the correct holes (shown in step A and B) using the 5/16 bolt with the matching nut and washer.

E. Install next puck (Side B) using the 1 3/4" woodscrews.

F. Continue until desired bump stop height (Side A/Side B/ Side A/Side B).






Step 8: Install Sway Bar Links / Drops

Note: Based on the kit you've purchased you will either have the Sway Bar Drop Bracket (7026) or the Sway Bar (7015).

Section 3: REAR SUSPENSION Installation Instructions

Step 9: Install 4" Rear Sway Bar Drop Bracket (Option 1 - 7026)

- A. Disconnect rear sway bar links from the sway bar only.
- B. Remove stock hardware from sway bar mounts.
- C. Fully remove the sway bar from the JK so that it no longer sits above the stock exhaust.
- D. Rear Sway Bar Drop Bracket
- E. Re-use the stock hardware to screw the drop bracket to the frame in the stock location. The bracket should be roughly vertical.
- F. Using the provided hardware use a 14mm or 9/16" hex socket or wrench to bolt the sway bar to the bottom of the drop bracket .
- G. Re-attach the stock sway bar links.



Section 3: REAR SUSPENSION Installation Instructions



Step 10: Install Rear Sway Bar (*Option 2 – 7015*)



- A. If you intend to replace your sway bar links with longer links, disconnect links on both ends.
- B. Slide the sway bar to the rear, or set aside.



Section 3: REAR SUSPENSION Installation Instructions



Step 10: Install Rear Sway Bar (Option 2 – 7015)




- C. Using the factory hardware install the bottom of the MetalCloak extended sway bar links.
- D. Using the factory hardware install the top of the MetalCloak extended sway bar links.
- E. Torque upper and lower bolts to 75lbs.

Section 3: REAR SUSPENSION Installation Instructions



Step 11: Install MetalCloak Track Bar Bracket

- A. Slide the MetalCloak Track Bar Bracket in place as shown and re-install the stock bolt through the control arm; do not fully tighten any hardware until the Bracket is fully installed.
- B. Insert the provided Spacer in the axle bracket where the stock track bar was mounted.
- C. Install the provided M14-2x100mm" Hex Cap Screw through the stock hole with a Washer under the head of the Screw.
- D. The Screw is backed by a M14" Nylon Jam LockNut and Washer; install but do not fully tighten.



Section 3: REAR SUSPENSION Installation Instructions






Step 11: Install MetalCloak Track Bar Bracket

- E. Use a 3/4" Socket to install the 1/2"-20 U-bolt with the provided 1/2"-20 Flange LockNuts. You can snug all the Bracket hardware at this time, but do not fully tighten.



Step 12: Install MetalCloak Track Bar

- A. Pre-set the length of the MetalCloak Track Bar to 40-1/8" eye-to-eye. This length can be adjusted for your specific build.
- B. Install the MetalCloak Track Bar using the stock hardware. On the bottom the BOLT HEAD should face REARWARD, and on the upper mount the NUT should be to the rear. Tighten all hardware.



Section 3: REAR SUSPENSION Installation Instructions



Step 13: Bleed Brake Lines

Important Note: *Before driving bleed brake lines.*



Section 3: REAR SUSPENSION Installation Instructions



Step 14: Rear Pinion Angle Adjustment *(if required)*

- A. The Control Arm lengths given are recommended as starting points **ONLY**. Your vehicle will tell you if the pinion needs to be adjusted. When you drive the Jeep for the first time after installing the lift or after installing a new drive shaft, if you notice rear drive line vibrations, pay attention to when the vibrations occur.
- B. If you notice vibrations during acceleration this would indicate that your pinion is too high. You can correct this condition by adjusting your rear upper control arms to a shorter length or by increasing the length of your rear lower control arms.
- C. If you notice Vibrations during Deceleration this would indicate that your pinion is too low. You can correct this condition by increasing the length of your rear upper control arms, or by adjusting the rear lower arms to a shorter length.